


Makita

SUGAR MILLS SOLUTIONS



SCAN ME



@makitalatinamerica



www.makitalatinamerica.com



Torque
1,800 N·m
(1,330 ft.lbs.)



XGT BL MOTOR XPT™

TW001G

40V MAX IMPACT WRENCH

- › 3/4" (19 mm)
- › 0 - 950 / 1,150 / 1,400 / 1,800 RPM
- › 0 - 1,900 / 2,200 / 2,400 / 2,500 IPM



Torque
730 N·m
(540 ft.lbs.)



XGT BL MOTOR XPT™

TW007G

40V MAX IMPACT WRENCH

- › 1/2" (12.7 mm)
- › 0 - 600 / 1,200 / 1,900 / 2,300 RPM
- › 0 - 1,200 / 1,900 / 2,700 / 2,900 IPM



Torque
350 N·m
(260 ft.lbs.)



XGT BL MOTOR XPT™

TW004G

40V MAX IMPACT WRENCH

- › 1/2" (12.7 mm)
- › 0 - 1,000 / 1,800 / 2,600 / 3,200 RPM
- › 0 - 1,800 / 2,600 / 3,400 / 4,000 IPM



Torque
1,050 N·m
(780 ft.lbs.)



LXI BL MOTOR

DTW1001

18V IMPACT WRENCH

- › 3/4" (19 mm)
- › 0 - 900 / 1,000 / 1,800 RPM
- › 0 - 1,800 / 2,000 / 2,200 IPM



Torque
700 N·m
(520 ft.lbs.)



LXI BL MOTOR XPT™

DTW700

18V IMPACT WRENCH

- › 1/2" (12.7 mm)
- › 0 - 500 / 1,200 / 1,900 / 2,200 RPM
- › 0 - 1,000 / 1,700 / 2,400 / 2,700 IPM



Torque
330 N·m
(240 ft.lbs.)



LXI BL MOTOR XPT™

DTW300

18V IMPACT WRENCH

- › 1/2" (12.7 mm)
- › 0 - 1,000 / 1,800 / 2,600 / 3,200 RPM
- › 0 - 1,800 / 2,600 / 3,400 / 4,000 IPM



DGP180

18V GREASE GUN

LXI™



- › 69 MPa (10,000 PSI)
- › Max flow rate: 290 mL/min (10.0 oz/min)
- › Variable speed trigger and lock-on button
- › Hose length: 120 cm (47-1/4")



Air bleed valve assists in faster pump priming



2 speed modes: Low and Auto-Speed



GD0600

DIE GRINDER

- › Collet: 6 mm (1/4")
- › Wheel Diameter: 38 mm (1-1/2")
- › 400W
- › 25,000 RPM



GD0800C

DIE GRINDER

- › Collet: 8 mm (1/4")
- › Wheel Diameter: 25 mm (1")
- › 750W
- › 7,000-28,000 RPM

SJS



XGT **BL**
MOTOR
XPT **AFT** (BRAKE)

GA004G

40V MAX ANGLE GRINDER

- › 115 mm (4-1/2") › Slide switch
- › 3,000 - 8,500 RPM



XGT **BL**
MOTOR
XPT **AFT**
(BRAKE) **AWS**

GA038G

40V MAX ANGLE GRINDER

- › 230 mm (9") › Trigger switch
- › 6,600 RPM



GA4550

ANGLE GRINDER

- › 115 mm (4-1/2")
- › Paddle switch
- › 1,300W › 11,000 RPM



9564PCV

ANGLE GRINDER

- › 115 mm (4-1/2")
- › Paddle switch
- › 1,400W › 2,800 - 12,000 RPM



GA9080

ANGLE GRINDER

- › 230 mm (9")
- › Trigger switch
- › 2,700W › 6,600 RPM



AFT (BRAKE)

GA9070

ANGLE GRINDER

- › 230 mm (9")
- › Trigger switch
- › 2,800W › 6,600 RPM



XGT
MOTOR **XPT** **AVT** **AFT** **AWS** **SOFT**
NOLOAD

HR001G

40V MAX SDS PLUS ROTARY HAMMER

- › 28 mm (1-1/8")
- › Impact energy: 2.8 J
- › 0 - 980 RPM
- › 0 - 5,000 BPM



XGT
MOTOR **BL** **XPT** **AVT** **AFT** **AWS** **SOFT**
NOLOAD

HR005G

40V MAX SDS MAX ROTARY HAMMER

- › 40 mm (1-9/16")
- › Impact energy: 8.0 J
- › 250 - 500 RPM
- › 1,450 - 2,900 BPM



XGT **X2**
MOTOR **BL** **XPT** **AVT** **AFT** **AWS** **SOFT**
NOLOAD

HR006G

80V MAX SDS MAX ROTARY HAMMER

- › 52 mm (2-1/16")
- › Impact energy: 20.0 J
- › 150 - 310 RPM
- › 1,100 - 2,250 BPM



AVT

SOFT

NOLOAD

HR4013C

SDS MAX ROTARY HAMMER

- › 40 mm (1-9/16")
- › 1,100W
- › Impact energy: 8.0 J
- › 250 - 500 RPM
- › 1,450 - 2,900 BPM



AVT

SOFT

NOLOAD

HR5212C

SDS MAX ROTARY HAMMER

- › 52 mm (2-1/16")
- › 1,510W
- › Impact energy: 20.0 J
- › 150 - 310 RPM
- › 1,100 - 2,250 BPM



XGT
MOTOR **BL** **XPT** **AVT** **AWS** **SOFT**
NOLOAD

HM001G

40V MAX SDS MAX DEMOLITION HAMMER

- › 15 lbs
- › Impact energy: 9.4 J
- › 0 - 2,600 BPM



XGT **X2**
MOTOR **BL** **XPT** **AVT** **AWS** **SOFT**
NOLOAD

HM002G

80V MAX SDS MAX DEMOLITION HAMMER

- › 28 lbs
- › Impact energy: 20.0 J
- › 950 - 1,900 BPM



AVT

SOFT

NOLOAD

HM1812

**HEX 1-1/8" (28.6 MM)
DEMOLITION HAMMER**

- › 70 lbs
- › Impact energy: 72.8 J
- › 2,000W
- › 870 BPM





XGT

ML003G

40V MAX LED WORKLIGHT

- › 1,100 / 450 lm
- › Up to 22 hrs of run time (w/ BL4040)
- › IP65 (Dust / water-resistant)



XGT XPT

ML007G

40V MAX LED FLASHLIGHT

- › 600 lm Spot, 1000 lm Flood, 1250 lm Spot/Flood & Strobe
- › Up to 10 hrs of run time on Spot (w/ BL4040)

TRIPOD LIGHT STAND

GM0002073



- › Telescopes to 1.930,4 mm
- › For use with ML003G, ML005G, DML811 y DML809



LXT X2 18V + 18V 36V

DML809

18V X2 LED CORDLESS/CORDED WORKLIGHT

- › 10,000 / 4,000 / 2,000 lm
- › Up to 8.5 hrs of run time (w/2 BL1860B)
- › IP65 (Dust / water-resistant)



LXT X2 18V + 18V 36V

DML810

18V X2 UPRIGHT LED LIGHT

- › 5,500 / 3,000 / 1,500 lm
- › Modes: 360°, 180° left, y 180° right
- › Up to 15 hrs of run time (w/ 2 BL1850B)
- › IP54 (Dust / water-resistant)



LXT

DML811

18V LED CORDLESS/CORDED WORKLIGHT

- › 3,000 / 1,500 / 750 lm
- › Up to 13 hrs of run time (w/ BL1860B)
- › IP65 (Dust / water-resistant)



LXT XPT

DML812

18V FLASHLIGHT

- › 600 lm Spot, 1000 lm Flood, 1250 lm Spot/Flood y 1200 lm Strobe
- › Up to 7 hrs of run time (w/ BL1850B)



LXT

DML814

18V TOWER WORK/MULTI-DIRECTIONAL LIGHT

- › 3,000 / 1,700 / 900 lm
- › Extends from 1,250mm to 2,240mm
- › Up to 10 hrs of run time (w/ BL1850B)
- › IP55 (Dust / water-resistant)



LXT

DML815

18V FLASHLIGHT

- › 160 lm
- › 12 position pivoting flashlight head
- › Up to 54 hrs of run time (w/ BL1860B)



DCU180

18V X2 POWER-ASSISTED WHEELBARROW



199116-7
Pipe frame



198494-2
Steel bucket



Holds 2x LXT® 18V Batteries but operates using 1 battery at a time




Easy to reach and use function control display and brakes



L.E.D. lights on each side of frame

LXT X2 18V + 18V 36V **BL** MOTOR **XPT**

- › Max. Load Capacity: 130 kg (290 lbs.)
- › Speed (High/Low): 0 - 3.5 / 0 - 1.5 km/h
- › Speed Reverse: 0 - 1 km/h
- › Climbing angle capacity: 12°



XGT **BL** MOTOR **XPT**

UB001G

40V MAX BLOWER

- › Air volume: 16.0 m³/min (565 CFM)
- › Air speed: 64 m/s (143 MPH)
- › Blowing force: 17 N
- › Cruise control lever with variable speed trigger

LXT **BL** MOTOR **XPT**

DUB184

18V BLOWER

- › Air volume: 13.0 m³/min (459 CFM)
- › Air speed: 52.1 m/s (116 MPH)
- › Blowing force: 10.9 N
- › Cruise control lever with variable speed trigger



XGT **BL** **MOTOR** **XPT**

UH008G

40V MAX HEDGE TRIMMER

- › Blade length: 600 mm (23-5/8")
- › Cutting capacity: 21.5 mm (7/8")
- › 0 - 2,000 / 3,600 / 5,000 SPM
- › 5-position rotating rear handle



XGT **BL** **MOTOR** **XPT**

UH006G

40V MAX HEDGE TRIMMER

- › Blade length: 600 mm (23-5/8")
- › Cutting capacity: 25.0 mm (1")
- › 0 - 2,000 / 3,000 / 4,000 SPM
- › 5-position rotating rear handle



LXT **BL** **MOTOR** **XPT**

DUH601

18V HEGDE TRIMMER

- › Blade length: 600 mm (23-5/8")
- › Cutting capacity: 23.5 mm (15/16")
- › 0 - 2,000 / 3,600 / 4,400 SPM
- › 5-position rotating rear handle



XGT **BL** **MOTOR** **XPT** **AFT** **ADT**

UR006G

40V MAX BRUSHCUTTER

- › Cutting capacity 430 mm (17")
- › 4,600 / 5,000 / 5,500 RPM
- › Similar to a 30cc gas engine



XGT **X2** **BL** **MOTOR** **XPT** **AFT** **ADT**

UR012G

80V MAX BRUSHCUTTER

- › Cutting capacity 480 mm (18-7/8")
- › 3,500 / 5,000 / 6,800 RPM
- › Similar to a 43cc gas engine

COUPLE SHAFT POWER HEADS



Lever style lock system allows for quick tool-less installation



3-speed options and variable speed trigger with reverse



LXT **X2** **18V + 18V 36V** **BL** **MOTOR** **XPT** **AFT**

DUX60

- › 18V X2
- › 0 - 5,700 / 8,200 / 9,700 RPM
- › Similar to a 24cc gas engine

XGT **BL** **MOTOR** **XPT** **AFT** **ADT**

UX01G

- › 40V MAX
- › 0 - 5,700 / 8,200 / 9,700 RPM
- › Similar to a 33cc gas engine

COMPATIBLE WITH A VARIETY OF MAKITA COUPLE SHAFT ATTACHMENTS

<p>Brushcutter EM404MP (198768-1) EM408MP (191K31-5)</p>	<p>Rotary scissors EM407MP (191M56-3)</p>	<p>Edger EE400MP (196749-9)</p>	<p>Pole saw EY403MP (191T40-0) 12"</p>	<p>Straight hedge trimmer EN410MP (197739-5)</p>	<p>Ground trimmer EN420MP (198059-0)</p>	<p>Cultivator KR400MP (195706-4)</p>	<p>Harvester EJ400MP (195720-0)</p>	<p>Power brush BR400MP (193318-5)</p>	<p>Power sweep SW400MP (193339-7)</p>	<p>Blower UB400MP (191F67-6) UB401MP (191P72-3)</p>	<p>1 mt shaft extension LE400MP (191E23-0)</p>
---	--	--	---	---	---	---	--	--	--	--	---



XGT **BL** MOTOR **XPT**™

UC013G

40V MAX CHAINSAW

- › Guide bar 450 mm (18")
- › Speed: 0-25.5 m/s (0-1,530 m/min)
- › Captured bar nut and lateral chain tensioning
- › Similar to a 42cc gas engine



LXT **BL** MOTOR **XPT**™ (BRAKE)

DUC254

18V CHAINSAW


- › Guide bar 250 mm (10")
- › Speed: 0 - 22.5 m/s (0 - 1,350 m/min) (0 - 4,430 FPM)
- › Captured bar nut and lateral chain tensioning
- › Similar to a 20cc gas engine



1,670 M²
(17,975 FT²)
(0.41 ACRES)

Cutting area
w/ 2x 5.0Ah 18V batteries

70L
(18GAL)



LXT **BL** MOTOR **XPT**™ (BRAKE)

DLM530

18V X2 LAWN MOWER

- › Cutting width: 534 mm (21")
- › Cutting height: 20 - 100 mm (13/16 - 3-15/16")
- › Mulching, bagging & side discharge
- › 2,300 - 2,800 RPM
- › Steel deck

REGULAR
1,670 M²
(17,975 FT²) (0.41 ACRES)
SELF-PROPELLED
1,416 M²
(15,240 FT²) (0.35 ACRES)

Cutting area
w/ 2x 5.0Ah 18V batteries

70L
(18GAL)



LXT **BL** MOTOR **XPT**™ (BRAKE)

DLM533

18V X2 SELF-PROPELLED LAWN MOWER

- › Cutting width: 534 mm (21")
- › Cutting height: 20 - 100 mm (13/16 - 3-15/16")
- › Mulching, bagging & side discharge
- › 2,300 - 2,800 RPM
- › Aluminum deck

CON PDC1200
6,900 M²
CON PDC01 (4 X DL1800B)
2,300 M²

Cutting area

70L
(18GAL)



CONNECTX **BL** MOTOR **XPT**™ **SOFT**
NOLOAD

LM001C

BATTERY POWERED SELF-PROPELLED LAWN MOWER

- › Powered by PDC01 and PDC1200 energy backpacks.
- › Cutting width: 534 mm (21")
- › Cutting height: 20 - 100 mm (13/16 - 3-15/16")
- › Mulching, bagging or side discharge
- › 2,300 - 2,800 RPM
- › Steel deck



DFV214


FAN VEST



LXT **BL MOTOR** **XPT™**

- › DFV214A01: Small – Large / DFV214A02: Xtra Large – 3XL
- › 4 air flow settings (turbo/high/medium/low)
- › Waterproof and breathable fabric
- › Antibacterial and deodorant lining

PORTABLE BACKPACK POWER SUPPLY



Wide padded adjustable straps and hip belt



L.E.D. battery charge indicator



Ideal for all day work



432 WH ENERGY OUTPUT



PDC01

- › Holds up four LXT batteries (not included)
- › Provides up to 4X the run time when used with Makita LXT 18V products
- › Provides up to 2X the run time when used with Makita LXT 18V X2 (36V) products



1,200 WH ENERGY OUTPUT



PDC1200

- › Integrated battery
- › Equivalent to having almost 14X LXT 18V batteries running at the same time
- › Ideal for heavy duty applications



CONNECT X™

DIRECT CONNECTION



XGT

WITH 40V ADAPTER (191N62-4)



LXT

WITH 18V ADAPTER (191A53-7)
WITH 18V X2 ADAPTER (191A52-9)

