



Cordless Driver Drill

DDF484

Cordless Hammer Driver Drill

DHP484



Durable Aluminum gear housing



Cordless Driver Drill
DDF484



Cordless Hammer
Driver Drill
DHP484



High speed
2,000rpm

Predecessor model: 1,550rpm

Compact overall length
182mm (DHP484)

Predecessor model: 199mm

Aluminum gear housing and all metal gear construction

for extra-high transmission durability



Compact overall length
DDF484: 172mm, DHP484: 182mm

21 Torque settings



Mechanical 2-speed gearing



Single sleeve keyless chuck

allows for easy bit installation/removal by one hand.

Capacity of drill chuck

1.5mm (1/16") - 13mm (1/2")

Twin LED job light with preglow and afterglow functions



Variable speed control by trigger

Best possible ergonomic handle with soft grip for driver-drill applications

- In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened to perfectly fit the U-shape formed between user's thumb and index finger.
- Newly designed slimmer grip provides comfortable grip with less fatigue.

Powered by the following 18V Li-ion batteries

with Battery fuel gauge



- BL1860B (6.0Ah)
- BL1850B (5.0Ah)
- BL1840B (4.0Ah)
- BL1830B (3.0Ah)
- BL1820B (2.0Ah)
- *BL1815N (1.5Ah)

*without Battery fuel gauge

Fast charger DC18RC



Charger DC18SD



Cordless Hammer Driver Drill DHP484



Cordless Driver Drill DDF484



Belt clip




Cordless Driver Drill	DDF484 13mm(1/2")
Cordless Hammer Driver Drill	DHP484 13mm(1/2")

	DDF484	DHP484
Variable Speed	Steel: 13mm (1/2") Wood: 38mm (1-1/2")	Steel: 13mm (1/2") Wood: 38mm (1-1/2") Masonry: 13mm (1/2")
Brake	-	-
Reversing	-	-
Mechanical 2-Speed	-	-
Keyless Chuck	-	-
Torque Setting 21	-	-
Built-in Job Light	-	-
Carrying Case	-	-
Capacity	Steel: 13mm (1/2") Wood: 38mm (1-1/2")	Steel: 13mm (1/2") Wood: 38mm (1-1/2") Masonry: 13mm (1/2")
Impacts per minute	-	Hi: 0 - 30,000 Lo: 0 - 7,500
No load speed (rpm)	Hi: 0 - 2,000 Lo: 0 - 500	Hi: 0 - 2,000 Lo: 0 - 500
Max. fastening torque	Hard / Soft: 54 / 30N·m	Hard / Soft: 54 / 30N·m
Dimensions (L x W x H)	172x79x244mm (with BL1815N) (6-3/4"x3-1/8"x9-5/8")	182x79x244mm (with BL1815N) (7-1/8"x3-1/8"x9-5/8")
	172x79x261mm (with BL1860B) (6-3/4"x3-1/8"x10-1/4")	182x79x261mm (with BL1860B) (7-1/8"x3-1/8"x10-1/4")
Net Weight	1.5kg (3.4lbs)(with BL1815N) 1.8kg (3.9lbs)(with BL1860B)	1.6kg (3.5lbs)(with BL1815N) 1.8kg (4.0lbs)(with BL1860B)

Standard Equipment: Belt Clip, (+)(-) bit, Battery, Charger

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.



Drilling (Wood/Metal) Accessories



Drilling (Masonry) Accessories



Fastening Accessories



Drill and Screw Bit Sets Accessories

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201608