



Cordless Worklight DML813 / DML814

Max luminous flux
3,000 lm

Max Height
2,240 mm

IP55
certified weather
and dust resistance

DML813

[Spot lighting]



DML814

[Spot lighting]



[Area lighting]



18V
LITHIUM-ION



Continuous run time (with BL1850B)

High	Medium	Low
3.0 h	5.5 h	10 h


3 brightness settings

High	Medium	Low
3,000 lm	1,700 lm	900 lm

Pivoting range of light head for Spot lighting



right and left
115°



up and down
110°

Pivoting range of 3 small light heads for area lighting



up and down
90°
DML814 only

Foldable into a compact size for simple storage and transport



1,000 mm

Push the unlock button to expand / fold the tripod base.

Shoulder belt
Attachable to the worklight or tool bag for comfortable carrying of the worklight



Accessories

Tool Bag



Shoulder Belt



2,240 mm



The height of light head can be adjusted steplessly



1,250 mm

18V LITHIUM-ION

DML814

Two lighting modes

Spot lighting / Area lighting

Battery capacity warning function

automatically notifies the user about reduction in battery capacity with the decrease of illuminance (Only one LED is on for notification).



DML813

Spot lighting

Easy installation and removal of battery



The battery port is located at the middle height of the worklight so that the user need not bend down to access the battery.

Padlock hole for battery theft protection




*Padlock not included

Three hook holes for the shoulder belt

Two hook holes are located on the carrying handle beside the battery, and one on the end of a tripod leg.

Tripod fixing hole



The tripod can be firmly secured to the ground with a screw or peg.

Cordless Worklight DML813 / DML814

Carrying Case

Run Time (hrs) w/ BL1850(B) Low / Mid / High: 10 / 5.5 / 3 at 1m from the light source: 1,250 / 750 / 400 lx
Illuminance (High / Mid / Low) at 3m from the light source: 130 / 80 / 40 lx
at 5m from the light source: 50 / 30 / 15 lx

Standard Equipment:
Shoulder Belt

Luminous Flux
Dimensions (L x W x H) Folding Position: 260x216x1,000 mm (10-1/4"x8-1/2"x39-3/8")
Operating Position (Max Height): 573x658x1,250-2,240 mm (22-1/2"x26"x49-1/4"-88")
Net weight DML813: 7.0 - 7.7 kg (15.4 - 17.0 lbs.)
DML814: 7.2 - 7.9 kg (15.9 - 17.4 lbs.)

Battery & Charger Sold Separately

The weight may differ depending on the attachment(s), including the battery cartridge.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202008