



Cordless Inflator
DMP180

Satisfy Professional's Needs



From daily maintenance to
outdoor activity.



Max air pressure

830 [121PSI]
kPa

Air Discharge Amount

12 [200kPa]
L/min

Net weight

1.7 [with BL1850B]
kg



Air Discharge Amount
12 L/min
[200kPa]

Net weight
1.7 kg
[with BL1850B]

18V LXT Li-Ion Cordless Inflator

Blows up air in the tires of cars/bikes



Max air pressure
830 kPa [121PSI]

PSI / bar / kPa can be changed
Pre-set pressure stop function



LED job Light
for easy operation at dark places.




Digital pressure gauge
provides high visibility with backlight.

Comes with valve adapters (with BL1850B)



Hose can be stored



Valve adapters

Valve shape	Car / Motorcycle	Bicycle	Road bike	Ball	Beach ball / Swim ring
Adapter	American	British	French	For Balls	For Swim rings/ Beach balls
Maximum air pressure: kPa	(approx.) 250	(approx.) 300	(approx.) 700	(approx.) 90	50 and under
Discharge amount: L/ min (at Target pressure)	283	13	25	25	33
a single full battery charge: count	Car tires (215/60R16) 9	Bicycle tires (Size-26inch) 166	Road bike tires (700x23c) 92	Soccer balls (Size-5) 142	Beach balls (dia.30cm) 121

Cordless Inflator

DMP180

Built-in Job Light	Max Air Pressure 830 kPa (121 PSI) [8.3 bar]
Carrying Case	Air Discharge Amount 200 kPa: 12 L/min
	Hose Length 65 cm (25-1/2")
	Dimensions (L x W x H) w/ BL1815N / BL1820B: 246x80x174 mm (9-11/16"x3-1/8"x6-7/8") w/ BL1830B / BL1840B / BL1850B / BL1860B: 266x80x174 mm (10-1/2"x3-1/8"x6-7/8")
	Net weight 1.4 - 1.7 kg (3.1 - 3.8 lbs.)

Standard Equipment : British Adapter, French Adapter, Ball Adapter, Swim Ring Adapter, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202001