




# 9" (230mm) Angle Grinder, with No Lock-On Switch

Model GA9060 / GA9060R\*

REDESIGNED 15.0 AMP MOTOR DELIVERS 6,600 RPM FOR OPTIMUM DURABILITY AND PERFORMANCE



## DESIGN

Motor engineered with greater stability resulting in longer life expectancy



## PERFORMANCE

Brush spiral spring allows for a 30% large brush and increases air-flow



## DURABILITY

Labyrinth construction protects the motor and bearings from dust and debris



## ERGONOMICS

Large spindle lock button for easier wheel changes



GA9060



GA9060R

\* with Anti-restart Function, Soft Start

## FEATURES

- Rear handle trigger switch with no lock-on feature; lock-off feature requires two actions to start the grinder
- Redesigned motor with greater armature stability and larger commutator bars for 3 times longer life compared to previous model
- Zig-zag epoxy on both sides of the armature coil and a powder-coated field for added protection from dust and debris for longer motor life
- Spiral bevel gears for smoother rotations and a more efficient transfer of energy
- Aluminum gear housing provides superior gear alignment and smoother transmission for increased durability
- Side handle installs in three locations for operator comfort in various applications
- With Anti-restart Function, Soft Start

## SPECIFICATIONS

|                     | GA9060              | GA9060R             |
|---------------------|---------------------|---------------------|
| Wheel Diameter      | 9" (230mm)          | 9" (230mm)          |
| AMPS                | 15                  | 15                  |
| No Load Speed       | 6,600 RPM           | 6,600 RPM           |
| Spindle Thread      | 5/8" - 11 UNC       | 5/8" - 11 UNC       |
| Lock-On             | No                  | No                  |
| Lock-Off            | Yes                 | Yes                 |
| Grinder Switch Type | Rear trigger handle | Rear trigger handle |
| Overall Length      | 17-3/4"             | 17-3/4"             |
| Net Weight          | 12.1 lbs.           | 12.4 lbs.           |
| UPC Code            | 088381-809962       | 088381-809993       |

## STANDARD EQUIPMENT

- 9" Wheel Guard (122938-0)
- Inner Flange (224317-9)
- Lock Nut (224486-6)
- Lock Nut Wrench (782412-6)
- Side Handle (143486-6)

## OPTIONAL ACCESSORIES

- 9" Tool-less Wheel Guard (122768-9)
- Grinding: 9" x 6mm x 7/8", Grit A24R, Depressed (741421-B)
- Metal Cutting: 9" x 2.5mm x 7/8", Grit A30S, Flat (A-85335)
- Metal Cutting: 9" x 3mm x 7/8", Grit A30S, Depressed (A-83624)
- Inox Cutting: 9" x 2mm x 7/8", Grit WA36R, Flat (D-21113)
- Inox Cutting: 9" x 2mm x 7/8", Grit WA36R, Depressed (D-18845)