

Cordless Rotary Hammer HR166D 16 mm (5/8")



SDS-PLUS shank





Powered by Slide Li-ion Battery of Makita's New 12Vmax Platform



Extremely Compact and Lightweight for increased maneuverability





Lightweight 1.8kg



Vibration absorbing housing

reduces the vibration to the hand.



LED job light

250 mm



Brushless motor

Tnakita





[LITHIUM+JON] 120

Accessories



Part No. 197224-8

Variable Speed
Brake
Reversing
Constant Speed

SDS-PLUS Shank
Dust Collecting

Built-in Job Light Carrying Case



Dust cup setUse with grip base se

Part No. 198362-9 198376-8 (EU)

HR166D



■ Li-ion Battery & Charging Time Reference

	-			
	XT AZVmax LITHIUM-JON	S AND SAND		
		*BL1041B	*BL1021B	BL1016
*with Battery fuel gauge		12Vmax 4.0Ah	12Vmax 2.0Ah	12Vmax 1.5Ah
Charging time	DC10SB	60 min	30 min	22 min
	DC10WD	130 min	70 min	50 min

Cordless Rotary Hammer

18V DHR242

,			
Impact Energy	EPTA-Procedure 05/2009: 1.1 J		
Capacity	Concrete: 16 mm (5/8")		
	Steel: 10 mm (3/8")		
	Wood: 13 mm (1/2")		
Impacts Per Minute (IPM)	0 - 4,800		
No Load Speed (RPM)	0 - 680		
Vibration Level	Hammer Drilling Into Concrete: 7.5 m/s ²		
	Drilling Into Metal: 2.5 m/s ² or less		
Sound Pressure Level	86 dB(A)		
Sound Power Level	97 dB(A)		
Dimensions (L x W x H)	250x74x187mm (9-7/8"x2-15/16"x7-3/8")		
Net weight	BL1016: 1.8 kg (4.0lbs.)		
	BL1041B: 2.0 kg (4.4 lbs.)		

weight according to EPTA-Procedure 01/ver.2.1

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

Dust Cup (country-specific), Side Grip, Depth Gauge, Battery, Charger