



Battery Powered Lawn Mower LM001C 534 mm (21") Self-Propelled



Long continuous operation



Mowing area (push-drive mode)

PDC1200

6,900 m²

PDC01
(BL1860B x4)

2,300 m²

PDC1200

Powered by
36V-40Vmax
built-in battery

PDC01

Powered by up
to four 18V
LXT batteries

Using Makita
Portable Power Pack



BL MOTOR XPT

Side discharge




with side discharge mouth

Cutting height is adjustable by one handle



BL MOTOR



PDC01 (Option)



PDC1200 (Option)

XPT

IPX4-rated water-resistance



Steel Deck

Control panel

- 3 cutting modes
 - Normal mode
 - Soft no-load mode
 - Noise reduction mode
- Main switch



Self-propelled type


Self-propelled speed: 2.5-5.0 km/h



Grass level indicator



Higher mowing performance



The blade is designed so that it tilts towards the front side of the mower when attached, preventing double-cutting for reduced current consumption.

Optimum blade design for less rotational speed reduction of the blade

Portable Power Pack

Portable Power Pack

PDC1200

Powered by 36V-40Vmax built-in battery



Charger DC4001



PDC01

Powered by up to four 18V LXT batteries



Battery Powered Line-up

Blower UB001C



Lawn mower LM001C



Grass Trimmer

UR101C
UR201C
UR202C



Accessories

Blade



Size: 530mm
Part No. 191D52-7



Swing back blade



Swing back blade 530 cpl. set
Size: 530mm
Part No. 191D50-1



Swing back blade 530 set (4 pcs)
Part No. 191D48-8

Battery Powered Lawn Mower

LM001C 534 mm (21") Self-Propelled

- Brake
- Electronic 2-Speed
- Constant Speed
- Soft Start

Standard Equipment:

Blade, Mulch Plug, Side Discharge Mouth, Box Wrench, Rod

| | |
|-------------------------------|--|
| Cutting Width | 534 mm (21") |
| Cutting Height | 20 - 100 mm (13/16 - 3-15/16") |
| Grass Box Capacity | 70 L |
| No Load Speed (RPM) | 2,300 - 2,800 |
| Propelling Speed | 2.5 - 5.0 km/h |
| Actual Mowing Area | w/ PDC01 (BL1860B X4), Self-Propelled: 1,700 m ² w/ PDC01 (BL1860B X4), push-drive: 2,300 m ² w/ PDC1200, Self-Propelled: 5,100 m ² w/ PDC1200, push-drive: 6,900 m ² |
| Continuous Use (min.) | w/ PDC01 (BL1860B X4), Self-Propelled: 40 w/ PDC01 (BL1860B X4), push-drive: 50 w/ PDC1200, Self-Propelled: 120 w/ PDC1200, push-drive: 150 |
| Sound Pressure Level | 80.0 dB(A) |
| Sound Power Level | 91.2 dB(A) |
| Vibration Level | 2.5 m/s ² or less |
| Dimensions (L x W x H) | 1,630 - 1,715 x 590 x 990 - 1,095 mm (64 - 67-1/2 x 23-1/4 x 39 - 43") |
| Net weight | 42.1 - 49.5 kg (92.8 - 109.1 lbs.) |

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202103