



Cordless Pole Saw series
UA001G / UA002G 250mm (10")
UA003G / UA004G 300mm (12")



photo: UA004G



photo: UA003G

Accessories

Guide bar / Saw chain / Guide bar cover



Cutter type: CC: Chamfer chisel

Guide Bar				Saw Chain					Bar Cover		Drive sprocket	
Bar length	Motor Mount	Type	Part No.	No. of drive links	Gauge	Pitch	Type OREGON	Cutter type	Part No.	Part No.	Type	Part No.
25cm/10"	A041	Sprocket nose bar	191G14-3	40	1.1mm / .043"	3/8"LP	90PX	CC	191H00-0	458501-6	Sprocket 3/8"LP	226992-7
30cm/12"			191G15-1	46					191H01-8	419288-5		
25cm/10"			191G22-4	40	1.3mm / .050"				191H08-4	458501-6		
30cm/12"			191G23-2	46					191H10-7	419288-5		

Band assembly set Part No. 191K37-5

The weight of the tool can be distributed on shoulders for reduced operator fatigue.



Portable Power Pack

PDC1200

Powered by 36V-40Vmax built-in battery



PDC01

Powered by up to four 18V LXT batteries



Adapter set

Part No. 191N62-4



Charging Time

Battery Model	Fast Charging	
	DC40RA	DC40RC
BL4020 2.0Ah	22 min	30 min
BL4025 2.5Ah	28 min	38 min
*BL4040 4.0Ah	45 min	67 min
*BL4050F 5.0Ah	50 min	85 min

*1 Recommended battery

Cordless Pole Saw	UA001G 250 mm (10")	UA003G 300 mm (12")
	Cordless Telescopic Pole Saw	
	UA002G 250 mm (10")	UA004G 300 mm (12")
Variable Speed	Variable Speed	
Brake	Brake	
Soft Start	Soft Start	
Standard Equipment: Saw Chain, Guide Bar, Blade Cover, Wrench, Band Assembly, Hex Wrench, Battery, Charger	Standard Equipment: Saw Chain, Guide Bar, Blade Cover, Wrench, Band Assembly, Hex Wrench, Battery, Charger	
Guide Bar Length	UA001G: 250 mm (10") UA003G: 300 mm (12")	UA002G: 250 mm (10") UA004G: 300 mm (12")
Saw chain	Gauge: 1.1 / 1.3 mm (0.043 / 0.050") Pitch: 3/8"	Gauge: 1.1 / 1.3 mm (0.043 / 0.050") Pitch: 3/8"
Chain Speed	0 - 20.0 m/s (0 - 1,200 m/min) (0 - 3,940 FPM)	0 - 20.0 m/s (0 - 1,200 m/min) (0 - 3,940 FPM)
Oil Tank Capacity	160 mL	160 mL
Dimensions (L x W x H)	without guide bar and Battery or with Battery BL4040 UA001G: 2,470 x 156 x 192 mm (97-1/4 x 6-1/8 x 7-9/16") UA003G: 2,526 x 156 x 192 mm (99-1/2 x 6-1/8 x 7-9/16")	without guide bar and Battery or with Battery BL4040 UA002G: 2,765 - 3,997 x 156 x 192 mm (109 - 157-1/2 x 6-1/8 x 7-9/16") UA004G: 2,812 - 4,044 x 156 x 192 mm (110-1/2 - 159 x 6-1/8 x 7-9/16")
Net weight	UA001G: 6.0 - 7.2 kg (13.2 - 15.9 lbs.) UA003G: 6.1 - 7.4 kg (13.4 - 16.3 lbs.)	UA002G: 7.7 - 8.9 kg (17.0 - 19.6 lbs.) UA004G: 7.8 - 9.1 kg (17.2 - 20.1 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 2021.12



High power
X
Long reach
||
High efficiency

250mm (10")
UA001G Fixed length
UA002G Telescopic

300mm (12")
UA003G Fixed length
UA004G Telescopic



Total length 2,230mm*
Fixed length

Telescopic
Total length 2,516 - 3,748mm*
*without guide bar

No load chain speed
20.0 m/s





***Saw head weight**
0.7 kg

Excellent tool balance
The motor is located in the battery housing at the bottom of the tool. This bottom-mounted motor reduces the saw head weight, allowing for:

- Ease to control the saw head for easy access to a desired cutting position
- Reduced user fatigue and stress

*without guide bar, saw chain and oil

Telescopic pole
(UA002G / UA004G only)
Tool-less pole extension and fixing for easy adjustment of pole length

BL MOTOR **High operating efficiency**

High power BL motor delivers the same or higher operation efficiency than 35mL class engine models.

AFT **Active Feedback sensing Technology**

Torque limiter turns the motor off if the tool is suddenly forced to lock

Speed
Time

Sudden reduction of rotational speed

Auto-Stop

Retractable oil tank cap knob decreases the chance that the saw head will be snagged in branches.

Slim saw head
The same slim design as engine pole saws provides easy maneuverability into branches.

Saw head width
87 mm

Chain oil tank with high transparency allows to easily check the amount of remaining oil.

Anti-fall captive nut

Integrated branch hook convenient for removing cut branches from trees

XPT / WG / IPX4
WET GUARD

High water-resistance allows to operate the machine even if it is wet with water.

Battery guard also can be used as an auxiliary grip.

250mm (10")	UA001G	Fixed length	300mm (12")	UA003G	Fixed length
	UA002G	Telescopic		UA004G	Telescopic

250mm (10")
300mm (12")

Maximum total length
3,748 mm
Shortest total length
2,516 mm

Total length
2,230 mm

Fixed length

photo: UA002G