

# Cordless Fan CF001G 40Vmax / AC




Noise level
48 dB
(A)
[in High speed]









#### **Automatic oscillation**





# Adjustable fan head angle



Up 90°, Down 45°, Left / Right 90°

### **Quiet running**

Changed the shape of corner rear fan cover to take the air smoothly to reduce the noise.



CF001G Predecessor



Model

Easy-to-clean-up fan blades

Front cover is removable simply by removing a single screw, allowing for convenient clean up.





#### **Carrying handle**



#### **AC** adapter jack



# **Charging Time Reference**



#### DC40RA

The enlarged and raised LED light provides clearer indication of charging status.





**BL4025** 2.5Ah

28<sub>min</sub>



**BL4040** 4.0Ah

45min

### **Cordless Fan**

#### CF001G 40Vmax / AC



Continuous Use (min.) w/o oscillation Continuous Use (min.) w/ oscillation
Max Air Velocity
Air Flow
Fan Diameter Dimensions (L x W x H)

Net weiaht

w/BL4040 Low / Mid / High: 1,160 / 880 / 660 w/BL4025 Low / Mid / High: 730 / 550 / 410 w/BL4040 Low / Mid / High: 1,055 / 800 / 600 w/BL4025 Low / Mid / High: 665 / 500 / 370 High / Mid / Low: 190 / 150 / 120 m/min High / Mid / Low: 8.2 / 6.5 / 5.2 m²/min 235 mm (9-1/4")

143x333x463 mm (5-5/8"x13"x18-1/4") 2.0 - 3.0 kg (4.4 - 6.6 lbs.)

Standard Equipment: AC Adaptor

The weight may differ depending on the attachment(s), including the battery cartridge.

Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan