



# Cordless Drywall Saw DSD180



**Suitable for straight cut  
in overhead application,**  
such as setting lights, air vents etc.



**Connectable to vacuum cleaners**

Cordless Backpack Vacuum Cleaner (DVC260) is option





### Base cover

protects drywall surfaces from damage/ scratches and keeps the machine balance during cutting.

### V-notch in base plate helps easy tracing of cutting line.



V-notch

Corner cutting can be easily done

Variable speed control by trigger allows easier start of cutting.

Battery fuel gauge

### Dust box

catches dust that drops through the base of base cover.

### Dust connector assembly

connectable to vacuum cleaner.

### LED job light

brightly illuminates the cut line for easy cutting of workpiece in the dark place.



### Cutting depth adjustment

#### Drywall



- Cutting depth can be adjusted to drywall thickness.
- Prevent accidental breakage of wires

### Blades



For dry wall  
Part No. B-49703

For wood  
Part No. B-49719

Option  
(Snap-off blade)

Compatible with both special blades for this drywall saw and option snap-off blades.

### Blade cover

protects drywall surfaces from damage/ scratches.



### Power by 18V Li-ion battery

with Battery fuel gauge

- BL1860B : 6.0Ah
- BL1850B : 5.0Ah
- BL1840B : 4.0Ah
- BL1830B : 3.0Ah



BL1850B

- BL1820B : 2.0Ah
- BL1815N\* : 1.5Ah

\*without Battery fuel gauge



BL1815N

#### Fast Charger

DC18RC



#### Charger

DC18SD



### Cordless Drywall Saw

#### DSD180

Variable Speed	<b>Strokes Per Minute (SPM)</b> 0 - 6,000
Orbital Cutting	<b>Length of Stroke</b> 6 mm (1/4")
Dust Collecting	<b>Capacity</b> Drywall: 30mm (1-3/16") Wood: 15 mm (9/16")
Built-in Job Light	<b>Max Output</b> 340W
Carrying Case	<b>Vibration Level</b> Cutting Drywall (thickness 30mm): 2.5 m/s <sup>2</sup>
	<b>Sound Pressure Level</b> 79 dB(A)
	<b>Dimensions</b> 263x79x291mm (10-3/8"x3-1/8"x11-3/8")
	<b>Net weight</b> BL1820B: 1.7 kg (3.8 lbs) BL1860B: 1.9kg (4.2lbs)

**Standard Equipment :** Blade, Blade cover, Base cover, Hex Wrench, Battery, Fast Charger

weight according to EPTA-Procedure 01/ver.2.1  
Items of standard equipment and specifications may vary by country or area.

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201606