

Equipped with catalytic muffler to comply with European exhaust emission regulations; EPA Phase 2 and EU Stage 2.

25.7ml
2-stroke engine
with 0.83kW of power

EM2600U

Ergonomic bike handle of off-set design

Designed so that the vertical center line of the handle bar stays aligned with that of ser

 Enables user to work in a comfortable posture with less fatigue throughout operation.

• Provides easy handling.





Spring-assisted recoil starter reduces the effort required for engine start.

Catalytic Converter



Ergonomically designed, large loop handle with soft grip

provides higher maneuverability, more comfort and better control while minimizing hand fatigue and pain.



Primer Pump Capacitor Discharge Ignition Capacitor Discharge Ignition Engine power 50:1 Fuel mixture 10:64 N8 x 1.25LH M8 x 1.25LH M9 x 1.25LH M8 x 1.25	Petrol Brushcutter	EM2600U / EM2600L 25.7mL		
CDI Capacitor Discharge Ignition			EM2600U	EM2600L
Capacitor Discharge Ignition Engine power 0.83kW/1.2PS 0.83kW/1.2PS 50:1 50:1 50:1 50:1 50:1 50:1 50:1 50:1	Primer Pump	Displacement	25.7mL	25.7mL
Discharge Ignition Fuel tank 0.6L 0.6L M8 x 1.25LH M8 x 1.25LH M8 x 1.25LH M8 x 1.25LH Sound pressure level 98.52db(A) 98.52db(A) 109.77db(A) 109.77db(A) Vibration level Left handle 14.680m/s² 8.83m/s² Vibration level Right handle 9.037m/s² 14.381m/s² Dimensions 1,770x610x410mm 1,770x310x235mm (L x W x H) (69-3/4"x24"x16-1/8") (69-3/4"x12-1/4"x9-Net weight* 5.0kg (11.0lbs) 4.9kg (10.8lbs)	Capacitor	Engine power	0.83kW / 1.2PS	0.83kW / 1.2PS
Spindle size		Fuel mixture	50:1	50:1
Sound pressure level 98.52db(A) 98.52db(A) Sound power level 109.77db(A) 109.77db(A) Vibration level Left handle 14.680m/s² 8.83m/s² Vibration level Right handle 9.037m/s² 14.381m/s² Dimensions 1,770x510x410mm 1,770x310x235mm (Lx W x H) (69-3/4"x24"x16-1/8") (69-3/4"x12-1/4"x9-Net weight* Net weight* 5.0kg (11.0lbs) 4.9kg (10.8lbs)		Fuel tank	0.6L	0.6L
109.77db(A)		Spindle size	M8 x 1.25LH	M8 x 1.25LH
Vibration level Left handle 14.680m/s² 8.83m/s² Vibration level Right handle 9.037m/s² 14.381m/s² Dimensions 1,770x610x410mm 1,770x310x235mm (LxWxH) (69-3/4"x24"x16-1/8") (69-3/4"x12-1/4"x9-Net weight* Net weight* 5.0kg (11.0lbs) 4.9kg (10.8lbs)		Sound pressure level	98.52db(A)	98.52db(A)
Vibration level Right handle 9.037m/s² 14.381m/s² Dimensions 1,770x610x410mm 1,770x310x235mm (L x W x H) (69-3/4"x24"x16-1/8") (69-3/4"x12-1/4"x9-Net weight* Net weight* 5.0kg (11.0lbs) 4.9kg (10.8lbs)		Sound power level	109.77db(A)	109.77db(A)
Dimensions 1,770x610x410mm 1,770x310x235mm (L x W x H) (69-3/4"x24"x16-1/8") (69-3/4"x12-1/4"x9-Net weight* Net weight* 5.0kg (11.0lbs) 4.9kg (10.8lbs)		Vibration level Left handle	14.680m/s ²	8.83m/s ²
(Lx W x H) (69-3/4"x24"x16-1/8") (69-3/4"x12-1/4"x9- Net weight* 5.0kg (11.0lbs) 4.9kg (10.8lbs)		Vibration level Right handle	9.037m/s ²	14.381m/s ²
Net weight* 5.0kg (11.0lbs) 4.9kg (10.8lbs)		Dimensions	1,770x610x410mm	1,770x310x235mm
		(LxWxH)	(69-3/4"x24"x16-1/8")	(69-3/4"x12-1/4"x9-1/4")
Standard Equipment :		Net weight*	5.0kg (11.0lbs)	4.9kg (10.8lbs)
Standard Equipment :				
Net weight: without guard, cutting tool, shoulder harness and fuel Nylon cutting head, Star blade, Hex Wrench, Socket wrench, + Screwdriv Single Harness		Nylon cutting head, Star bla	de, Hex Wrench, Socket	wrench, + Screwdriver,

