





## Powered by Slide Li-ion Battery of Makita's New 10.8V Platform



# Two switch levers are available with variable speed control.

Multi-position switch to make operation easier at any grip position for versatile applications by pulling either trigger.











**JR103D** 

Toolless blade clamp for Recipro saw blade





**JR105D** 

Blade clamp compatible with both Recipro and Jig saw blades



▲ On-tool storage for hex wrench



LED job light



#### Li-ion Battery & Charger Time Reference, Compatibility Chart



#### ■ Performance Comparison

Note: 1. The test results depend to a great extent on the hardness of materials, etc.

2. The numbers in the bar graphs are relative values when the capacity of **Competitor "M"** is indexed at 100.

<b>Test material:</b> EMT steel p	pe of ø25.4m	m (1")		
Work speed ← slow		fast →		
Makita JR103/JR	05D			150
Competitor "D"			127	
Competitor "M"		100		
0 5	0	10	00	150

#### **Battery fuel gauge**

(BL1020B, BL1040B)

The power remaining in the battery can be indicated in 4 stages simply by pushing a button.



Battery fuel gauge (4 stage LED)

#### Forced air cooling system

DC10SA only

• Stand-by time until the charge starts can be greatly shortened by using charger DC10SA equipped with a

built-in cooling fan.
•Effectively cools
down every battery
cell with the forced
air cooling system
and the heat sinks.



### Cordless Recipro Saw JR103D/ JR105D

Variable Speed

Brake

Bayonet Shank

Bayonet Shank Jig Saw Blade (JR105D only)

Built-in Job Light

Carrying Case

Capacity

Length of stroke Strokes per minute (spm) Dimensions (L x W x H) Net weight\*

Pipe:50mm (2") Wood:50mm (2") 13mm (1/2") 1) 0-3,300 376x66x186mm (14-3/4"x2-5/8"x7-3/8") BL1015: 1.3kg (2.9lbs) BL10408: 1.5kg (3.3lbs)

Standard Equipment :

Battery, Charger, Battery cover, Hex wrench, Recipro saw blades

\*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.







