







# **Hot Water, Anytime Anywhere**











## **Powered by 40Vmax XGT Li-Ion battery**

Battery box is able to hold two XGT series batteries.



Easy to carry around



Kettle can be transferred easily on Power supply stand by holding the carrying handle of the stand.

#### **Dual layer structure**



Stainless steel interior plus plastic exterior\* provides high heat retention while keeping Kettle surface cool.

\*There is a insulating layer of air between the interior and exterior layers.

#### Removable lid



Removable for easy water supply and cleaning

Anti-spill lock button



Provided to minimize spilling of hot water even if Kettle falls over.

#### Easy to read water scale



Kettle can be turned on only when grounded.



• Auto shut-off after boiling Boil-dry protection

capacity 0.8 L

Water tank

**Boiling time** (approx.)

8 min

Battery BL4040 x2





## Portable Power Pack

## PDC1200 Powered by 36V-40Vmax built-in battery



Adapter set (40Vmax)

Part No. 191N62-4



## Line up

LED Flashlight

ML002G



**Job Site Radio** 



**Cordless Cooler & Warmer Box** 



## Accessories

### Cup

Part No. KF00000020 Capacity: 240mL



## **Charging Time**

40 Visson	DC40RA	DC40RC
*1 <b>BL4020</b> 2.0Ah	22 min	30 min
*1 <b>BL4025</b> 2.5Ah	28 min	38 min
*1 <b>BL4040</b> 4.0Ah	45 min	67 min
*1 <b>BL4050F</b> 5.0Ah	50 min	85 min
*1 <b>BL4080F</b> 8.0Ah	76 min	170 min

\*1 Recommended battery

## **Cordless Kettle**

## **KT001G**

Water Tank Capacity Dimensions (L x W x H) 800 mL 233 x 322 x 307 mm (9-1/8 x 12-5/8 x 12-1/8") 2.8 - 5.9 kg (6.2 - 13.0 lbs.) Net weight

Approx amount of hot water for making drinks/foods			
Instant/drip coffee	0.2 L		
Instant cup soup	0.15-0.23 L		
Instant cup noodles	0.3-0.5 L		

Boiling time (approx.) of 0.8L water			
Water temperature	10°C	23°C	40°C
Boiling time	9 min	8 min	6 min

not covered by EPTA-Procedure Items of standard equipment and specifications may vary by country or area.

## Makita Corporation