

Cordless Portable Band Saw PB002G





Max. cutting capacity 127mm



Cutting work amount Battery: BL4040 Work volume on a single full battery charge carbon steel pipe with an outer diameter of 114.3mm and a thickness of 6.0mm

31_{pcs}







Variable speed control by dial

An optimum cutting speed can be selected to suit application.



Twin LED light

with preglow and afterglow functions



Tool hook

Convenient for cutting the pipes near the wall or the floor.



Easy installation/removal of blade











Accessories

Band saw blade

Length: 1140mm





Carbon steel (3pcs./set)

Material thickness	Трі	Teeth shape	Material	Part No.
	6		Wood	792567-9
More than 5 mm	14		Plastics and	792560-3
4 mm - 5 mm	18		non-ferrous metal. Mild steel, cast	792559-8
Less than 4 mm	24		steel and cast iron.	792558-0

Bi-Metal (1pc.)

Material thickness	Tpi	Teeth shape	Material	Part No.
More than 5.5 mm	10		Plastics and non-ferrous metal. Mild steel, cast steel and cast iron.	B-30128
More than 5 mm	14	ALAD		792557-2
				194691-8
4 mm - 5 mm	18		Hard steel and	792556-4
Less than 4 mm	24		stainless steel.	194692-6

Charging Time

40 Visson	DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040 4.0Ah	45 min	67 min
BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

^{*1} Recommended battery

Cordless Portable Band Saw

PB002G Variable Speed Capacity Round: 127 mm (5") Square: 127 x 127 mm (5 x 5") 0 - 3.2 m/min (0 - 630 ft/min) (Brake Blade Speed Blade Size Constant Speed Length: 1,140 mm (45") Width: 13 mm (1/2") Thickness: 0.5 mm (0.02") Cutting Metal: 2.5 m/s² or less Soft Start Vibration Level 78 dB(A) w/ BL4020 / BL4025 /BL4040 : 510 x 218 x 314 mm Sound Pressure Level Dimensions **≣**○ Built-in Job Light W/ BL4080F: 510 x 218 x 346 (20 x 8-5/8 x 13-5/8") W/ BL4080F: 510 x 218 x 346 (20 x 8-5/8 x 13-5/8") $(L \times W \times H)$ Carrying Case Net weight 6.6 - 7.8 kg (14.6 - 17.2 lbs.)

Standard Equipment: Band Saw Blade, Hex Wrench, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation