Satisfy Professional's Needs



Cordless Multi Tool TM30D

Tnakita



Compact & Lightweight



Compatible with all OIS accessories (Oscillating Interface System)



A Wide

2

Powered by Slide Li-ion Battery of Makita's New 10.8V Platform





effectively illuminates the tip of accessory in dark, tight spaces



Variable speed control by dial



Dust extraction system available as an option for aggressive dust removal in applications with sanding pad.



Li-ion Battery & Charger Time Reference, Compatibility Chart

CXT.	BL1015 10.8V 1.5Ah	BL1020B 10.8V 2.0Ah with Battery fuel gauge	BL1040B 10.8V 4.0Ah with Battery fuel gauge
DC109 for 10.8	22min	30 _{min}	60 min
DC10V for 10.8	50min	70 min	130 min

Battery fuel gauge

(BL1020B, BL1040B)

The power remaining in the battery can be indicated in 4 stages simply by pushing a button.



Battery fuel gauge(4 stage LED)



Multi tool Accessories

Forced air cooling system

DC10SA only

·Stand-by time until the charge starts can be greatly shortened by using charger DC10SA equipped with a built-in cooling fan. •Effectively cools down every battery cell with the forced air cooling system and the heat sinks.



Cordless Multi Tool TM30D Oscillations per minute (opm) 6,000 - 20,000 🚳 Variable Speed Oscillation angle Circumference of grip 168mm (6-5/8") 9 Soft start 88mm (3-1/2") 277x65x98mm Head height Dimensions Dust Collecting $(L \times W \times H)$ (10-7/8"x2-9/16"x3-7/8", 170W Max Output BL1020B: 1.1kg (2.4lbs) Net weight BL1040B: 1.2kg (2.7lbs) Carrying Case

Standard Equipment : Oscillating multi tool accessories, Hex Wrench, Battery, Fast Charger, Dust attachment (country-specific), Tool box (country-specific)

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area. Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan