





40Vmax mechanism movie



This movie was filmed in Japan. Models and specs may vary by country.

Portable Power Pack

PDC01

Powered by up to four 18V LXT batteries





PDC1200

Powered by 36V-40Vmax built-in battery







Adapter set (40Vmax)



Cordless Grass Trimmer UR002G / UR003G





12pcs. set

Part No. 191D89-4 Cord/Line: 2.0mm x4m

Ref.: UN-74L





198893-8 (EU)

Ref.: ECO 4L

Part No. 197804-0 197993-1 (EU) Cord/Line: 2.4mm x3m



Brushcutter blade

3-tooth blade Part No. 195298-3 Blade dia.: 230mm



with nut

M10x1.25 LH





Four-leaf Spiral Nylon cord



Green			
	Size	Part No	
	2.0mmx15m	197472	
	2.0mmx30m	197473	
	2.0mmx160m	197474	
	2.0mmx280m	197475	

reen		Orange		
Size	Part No.	Size	Part No.	
2.0mmx15m	197472-9	2.4mmx15m	198501-1	
2.0mmx30m	197473-7	2.4mmx30m	198502-9	
2.0mmx160m	197474-5	2.4mmx120m	198503-7	
2.0mmx280m	197475-3	2.4mmx180m	198504-5	

Protection guard for brush cutting blades

Part No. 197294-7





Shoulder strap assembly

Part No.122906-3









Charging Time Reference

40Vmax	DC40RA FASEC/Gregory	DC40RC
BL4020 2.0Ah	22 _{min}	30 _{min}
*1 BL4025 2.5Ah	28 _{min}	38 _{min}
*1 BL4040 4.0Ah	45 _{min}	67min
*1 BL4050F 5.0Ah	50min	85min

Cordless Grass Trimmer



The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202104







High power as 25mL engine tool





Outer Rotor BL Motor provides high operating efficiency

Constant speed

Aluminum motor housing

Direct drive system


for more power, more speed and longer run time

High rotation speed 6,500 min⁻¹

ADT

Automatic torque Drive Technology

Automatically changes the cutting speed according to grass density.




AFT

Active Feedback sensing Technology

עוושואלנדש

stator

Torque limiter turns the motor off if the tool is suddenly forced to lock



The vertical center line of the handle bar always stays aligned with that of user (UR002G only)



- enabling user to work with less fatigue even in long continuous operation.
- allowing for a wider swing.

Multi functional control panel: near right hand position for easy access and operation



Electronic 3-speed

Reverse button / ADTMain power button

Operation mode can be selected to suit the type of blade.



Plastic blade mode

Nylon cord mode

Large push button main power switch allows for easy on/off

Work amount

on a single full battery charge about 290 m²

Work amount depends on the condition of battery, the type of grass, season, etc.

Run Time*

Nylon cutting head

High Med Low

45 / 80 / 259 min with BL4050F


*on a single full battery charge / No load

Reverse switch



Reverse switch for clearing entangled weeds and grass from cutting head

Toolless handle lock mechanism for good portability





WET GUARD



High water-resistance allows to operate the machine even if it is wet with water.



eXtreme Protection Technology

Enhanced Dust and Drip-proof Performance ensure reliable operation even under bad weather



even with gloved hand.

