



Satisfy Professional's Needs

Cordless Rotary Hammer DHR165 / DHR164 16mm (5/8")



Adapted for
SDS-PLUS bit

18V
LITHIUM-ION

14.4V
LITHIUM-ION

LXT
LITHIUM-ION


Lightweight and compact design



Hammering
with
Rotation

2

mode



Rotation



Photo: DHR165

Tool does not come with bit.

Ergonomic handle for perfect tool control and minimum hand fatigue and pain.



Adapted for SDS-PLUS bit

Compact **297 mm (11-3/4")**



Ribbed soft grip




In-line positive grip design maximizes power thrust.

One touch sliding chuck for easy bit changes

Torque limiter

Reverse switch

Variable speed control by trigger



Single-light LED job light with afterglow function

- On pulling switch trigger, the light automatically turns on before motor starts turning.
- keeps on illuminating about 12-13 sec. after trigger release



Photo : DHR165



Power by Li-ion batteries

DHR165

BL1850 (5.0Ah), BL1840 (4.0Ah), BL1830 (3.0Ah), BL1820 (2.0Ah), BL1815N (1.5Ah)

DHR164

BL1440 (4.0Ah), BL1430 (3.0Ah), BL1430A (3.0Ah), BL1415NA (1.5Ah)

Charger

DC18RC



Two Port Multi Fast Charger DC18RD



Charging time (3.0Ah) 22minutes

Four Port Multi Charger DC18SF

Charging time (4.0Ah) 1 to 2 batteries : 90minutes 3 to 4 batteries : 180minutes



DC18SD

Charging time (4.0Ah) 90minutes



DC18SE (Automotive)

Charging time (4.0Ah) 90minutes



Lightweight

2.2kg

(4.9lbs)

DHR165 with BL1815N



Photo : DHR164

Cordless Rotary Hammer

DHR165 / DHR164 16mm (5/8")

430 RPM

- Variable Speed
- Brake
- Reversing
- Adapted for SDS-PLUS bits
- Torque Limiter
- Dust Collecting
- Built-in Job Light
- Carrying Case

Capacity

Concrete : 16mm (5/8")

Steel : 13mm (1/2")

Wood : 24mm (15/16")

Impacts per minute (ipm)

0 - 5,300

No load speed (rpm) 0-1,600

Dimensions (L x W x H)

BL1830, BL1840, BL1850: 297x79x253mm (11-3/4"x3-1/8"x10")

BL1815N, BL1820: 297x79x236mm (11-3/4"x3-1/8"x9-1/4")

BL1830, BL1840, BL1850: 2.5kg (5.5lbs)

BL1815N, BL1820: 2.2kg (4.9lbs)

Net weight

DHR165

Concrete : 16mm (5/8")

Steel : 13mm (1/2")

Wood : 24mm (15/16")

0 - 5,300

0-1,600

BL1430, BL1430A, BL1440: 297x79x250mm (11-3/4"x3-1/8"x9-7/8")

BL1415NA, BL1415N: 297x79x235mm (11-3/4"x3-1/8"x9-1/4")

BL1430, BL1430A, BL1440: 2.4kg (5.3lbs)

BL1415NA, BL1415N: 2.2kg (4.8lbs)

Tool does not come with bit.

Standard Equipment : Fast charger, Battery cartridge, Side grip, Depth gauge

weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BE-BA