Satisfy Professional's Needs



Cordless Impact Driver DTD153

makit

RUSHLE



High Performance with Brushless DC Motor.

Max tightening torque



Lightweight at







Aluminum hammer case

creates impression of rigidity.

One-touch bit installation

(For some countries only) No need to pull bit sleeve for bit installation

Twin LED Job light with pre-glow and afterglow functions









Variable speed control by trigger

Ergonomically designed handle with soft grip

provides comfortable grip and more control while minimizing hand fatigue and pain.

Powered by **18V Li-ion batteries**





Option **Tool catcher set**

enables to hook the machine quickly on a snap hook of waist belt.





Part No. 195798-3

Part No. 197043-2

Battery Protector

designed to protect the battery cartridge from dust and dripping water in outdoor applications or harsh environments.



Battery / Charger with Battery fuel gauge



*without Battery fuel gauge

Cordless Impact Driver DTD153

Variable Speed

Brake

Reversing

Carrying Case

BL1860B (6.0Ah) BL1850B (5.0Ah) BL1840B (4.0Ah) BL1830B (3.0Ah) BL1820B (2.0Ah) *BL1815N (1.5Ah)

Capacity

Impacts per minute (ipm) No load speed (rpm)

Max. fastening torque Vibration Level

Sound Pressure Level Sound Power Level

Dimensions (L x W x H) Net weight







M4 - M8 (5/32" - 5/16") M5 - M16 (3/16" - 5/8") M5 - M14 (3/16" - 9/16") Machine screw : Standard bolt : High strength bolt: Coarse thread (in length) : 22 - 125mm (7/8" - 4-7/8") 22 - 12511111 (7/8 - 4-7), 0 - 3,600 0 - 3,400 170 N·m (1,500 in·lbs) 13.0 m/s² 96 dB(A) 107 dB(A) 126x79x238mm (5"x3-1/8"x9-3/8") BL1850B : 1.5kg (3.3lbs) BL1815N: 1.3kg (2.8lbs)

Standard Equipment : Belt Clip, Battery, Fast Charger

weight according to EPTA-Procedure 01/ver.2.1 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan