



Makita

UTILITIES SOLUTIONS

FOR ELECTRICITY, NATURAL GAS, SEWER

    [makitalatinamerica](https://www.makitalatinamerica.com)



OVER 100 YEARS OF INNOVATION

As the innovation leader, Makita leads the industry with best-in-class quality cordless products. Makita's cordless products deliver the power, speed, and run-time to handle any project from wood and metalworking to concrete and dust extraction. From the job site to your home, Makita offers a wide range of cordless products ready to use anytime, anywhere.

TECHNOLOGIES



BRUSHLESS MOTOR

Eliminates carbon brushes, enabling the BL™ Motor to run cooler and more efficiently for longer life and maximum performance



EXTREME PROTECTION TECHNOLOGY

XPT is a series of integrated seals engineered to channel away dust and water for increased durability in harsh conditions.



ANTI-VIBRATION TECHNOLOGY

AVT is a counterbalance system inside the tool that reduces vibration for user safety with no compromise in power and performance



AUTOMATIC TORQUE DRIVE TECHNOLOGY

Adjusts speed and torque for optimal performance, even in the most demanding applications.



ACTIVE FEEDBACK-SENSING TECHNOLOGY

Electronically turns off the motor if rotation of the attachment is suddenly forced to stop to minimise the effect of kick-back.



AUTO-START WIRELESS SYSTEM

Uses Bluetooth® technology for wireless power-on and power-off communication between the equipped tool and dust extractor.



DEEP AND EXACT CUTTING TECHNOLOGY

More cutting capacity and out-of-the-box accuracy for superior cutting performance.



SUPPRESSION OF MOTOR SPEED

Reduces RPM and vibration creating a more accurate starting for user convenience



SUPER JOINT SYSTEM

SJS is a mechanical clutch system that helps prevent motor and gear damage in grinders if the wheel is forced to a stop for safety and durability.



SUPER JOINT SYSTEM II

SJS II is a leaf spring and cam gear drive mechanism in grinders that is engineered to reduce vibration for increased user comfort during extended use.



MOST POWERFUL SYSTEM

Engineered to achieve the optimum power required for heavier load applications. These high-powered products are the one-battery solution to handle the most demanding jobs and environments.

OUTPOWER



OUTSMART



OUTLAST



40V MAX



80V MAX



125+ PRODUCTS*
ONE SYSTEM



WORLD'S LARGEST 18V SYSTEM

ONE SYSTEM. ENDLESS POSSIBILITIES
Makita's Brushless Motor, battery technology, and enhanced communications work together to deliver maximum performance and efficiency for every trade

LXT BATTERY
MORE RUN TIME



LXT RAPID CHARGER
FASTER CHARGING



BRUSHLESS MOTOR
LONGER MOTOR LIFE



STAR PROTECTION
COMPUTER CONTROLS
EFFICIENT POWER



18V



36V



320+ PRODUCTS*
ONE SYSTEM



XGT

UC004G

WITH HIGH POWER-TO-WEIGHT RATIO DESIGNED FOR IN-TREE WORK. DELIVERS UP TO 160 CUTS IN 4X4 CEDAR WITH 40V MAX XGT 4.0AH BATTERY



XGT **BL** MOTOR **XPT** **BRAKE**

UH006G 40V Max Hedge Trimmer

- 5-position rotating rear handle
- Sharp-edged shear blade for thick and hard branches
- Anti-vibration design

Blade Length 600 mm (23-5/8")

Max Cutting Capacity 25.0 mm (1")

2,000 / 3,000 / 4,000 SPM



XGT **BL** MOTOR **XPT** **BRAKE**

UH008G 40V Max Hedge Trimmer

- 5-position rotating rear handle
- Standard Blade
- Anti-vibration design

Blade Length 600 mm (23-5/8")

Max Cutting Capacity 21.5 mm (7/8")

2,000 / 3,600 / 5,000 SPM



XGT **BL** MOTOR **XPT** **BRAKE**

UC004G 40V Max Chain Saw

- Up to 25% faster than gas
- Adjustable automatic chain lubrication
- Variable speed trigger

Guide Bar Length 350 mm (14")

Chain Gauge 1.1 mm (0.043")

Chain speed 0 – 4,880 FPM



XGT **BL** MOTOR **XPT** **BRAKE** **AFT**

UA004G 40V Max Pole Saw

- Delivers the power of a 35cc gas pole saw
- Adjusts length from 2.5m to 3.8m (9 ft. to 13 ft)

Guide Bar Length 300 mm (11-3/4")

Chain Gauge 1.3 mm (0.050")

Chain speed 3,940 FPM



LXT **BL MOTOR** **XPT** **BRAKE**

DUH601
18V Hedge Trimmer

- 5-position rotating rear handle
- Optimum blade shape for smooth cutting
- Anti-vibration design

Blade Length 600 mm (23-5/8")
Max Cutting Capacity 23.5 mm (15/16")
2,000 / 3,600 / 4,400 SPM



LXT **BL MOTOR** **XPT** **BRAKE**

DUH606
18V Hedge Trimmer

- Power to cut thick branches
- Double-sided steel blade provides optimal performance
- Less weight than gas models

Blade Length 600 mm (23-5/8")
Max Cutting Capacity 20 mm (13/16")
4,000 SPM



LXT **XPT**

DUN461W
18V Pole Hedge Trimmer

- 10 angle head settings
- Adjusts length from 1.8m to 2.4m (6 ft. to 8 ft)
- Less weight than gas models

Blade Length 460 mm (18-1/8")
Max Cutting Capacity 18 mm (11/16")
3,600 SPM



LXT **BL MOTOR** **XPT** **BRAKE**

DUN500W
18V Pole Hedge Trimmer

- 6 angle head settings
- Double-sided shear blade for optimal performance
- Soft grip handle

Blade Length 500 mm (19-3/4")
Max Cutting Capacity 23.5 mm (15/16")
2,000 / 3,600 / 4,400 / SPM



LXT **BL MOTOR** **XPT** **BRAKE**

DUC254
18V Chain Saw

- Torque boost mode for cutting dense material
- Automatic chain lubrication
- Compact top handle design

Guide Bar Length 250 mm (10")
Chain Gauge 1.1 mm (0.043")
Chain speed 0 - 4,720 FPM



LXT **X2** **18V + 18V 36V** **BL MOTOR** **XPT** **BRAKE**

DUC306
36V Chain Saw

- Torque boost mode for cutting dense material
- Automatic chain lubrication
- Equivalent to a 30cc gas chain saw

Guide Bar Length 300 mm (12")
Chain Gauge 1.1 mm (0.043")
Chain speed 0 - 3,940 FPM



LXT **X2** **18V + 18V 36V**

DUA301
36V Pole Saw

- 20% faster cutting speed than a 31.4cc gas engine pole saw
- Adjusts length from 2.6m to 3.8m (9 ft. to 13 ft)
- Torque boost mode powers through thick or hard branches
- Branch hook for pulling trimmed branches from trees

Guide Bar Length 300 mm (12")
Chain Gauge 1.1 / 1.3 mm (0.043 / 0.050")
Chain speed 0 - 3,940 FPM

HEDGE TRIMMER ACCESSORIES



199099-1
Shear blade 600mm
For DUH601



1910H9-0
Shear blade 600mm
For DUH606



191P00-8
Shear blade 460mm
For DUN461W



191C14-9
Shear blade 500mm
For DUN500W



191R55-5
Shear blade 600mm
For UH006G



191R57-1
Shear blade 600mm
For UH008G

CHAIN SAW ACCESSORIES



191G14-3
Sprocket Guide Bar
10" 3/8" .043



191H00-0
Saw Chain 10" 3/8"
.043" 90PX



191G15-1
Sprocket Guide Bar
12" 3/8" .043



191H01-8
Saw Chain 12" 3/8"
.043" 90PX



191G16-9
Sprocket Guide Bar
14" 3/8" .043



191H02-6
Saw Chain 14" 3/8"
.043" 90PX

For DUC254, DUC306, DUC406, UC004G, DUA301, UA004G

For DUC254, DUC306, DUC406, DUC407, DUC353, DUC355, UC004G, UC013G, DUA301, UA004G

For DUC306, DUC406, DUC407, DUC353, DUC355, UC004G, UC013G

XGT**UX01G**

COMPATIBLE WITH A VARIETY OF MAKITA COUPLE SHAFT
ATTACHMENTS FOR VARIOUS APPLICATIONS

ULTIMATE VERSATILITY

THE MAKITA COUPLE SHAFT SERIES HAS MULTIPLE ATTACHMENTS THAT ARE FULLY COMPATIBLE WITH THE GAS ENGINE OR CORDLESS POWERHEAD. THESE TOOLS GIVE YOU INCREASED EFFICIENCY AND REDUCED COSTS BY USING ONE POWER HEAD SYSTEM FOR MULTIPLE APPLICATIONS.

THE LEVER STYLE LOCK SYSTEM ALLOWS FOR QUICK TOOL-LESS INSTALLATION AND REPLACEMENT OF ATTACHMENTS.



XGT **BL MOTOR** **XPT** **BRAKE** **AFT**

UX01GZ01
40V Max Couple Shaft Power Head

- Delivers power of 30cc gas string trimmer
- 3-speed options and variable speed trigger for power management
- Up to 2X longer sustained power under heavy-load applications

0 - 5,700 / 0 - 8,200 / 0 - 9,700 RPM

Max output 1,000 W

INCLUDES 198768-1 (EM404MP) Brushcutter attachment



LXT
X2 18V + 18V 36V

BL MOTOR **XPT** **BRAKE** **AFT**

DUX60
36V Couple Shaft Power Head

- Delivers power of 24cc gas string trimmer
- 3-speed options and variable speed trigger for power management
- Maximum performance and run time without leaving the 18V battery platform

0 - 5,700 / 0 - 8,200 / 0 - 9,700 RPM

Max output 600 W

Compatible with a variety of Makita couple shaft attachments

PICK YOUR ATTACHMENT



191N31-5 (EM408MP)
Grass trimmer



ACCESSORIES
197804-0
Nylon Cutting Head




198768-1 (EM404MP)
Brushcutter



191T40-0 (EY403MP)
12" Pole Saw

ACCESSORIES

	
191G15-1 Sprocket Guide Bar 12" 3/8" .043	191H01-3 Saw Chain 12" 3/8" .043" 90PX



197739-5 (EN410MP)
20" Hedge Trimmer

ACCESSORIES


197768-8 Shear blade



191E23-0 (LE400MP)
1m (42") Shaft extension



UC013G

NO GAS, EMISSIONS, OIL MIXING OR PULL STARTS WITH REDUCED MAINTENANCE AND LOW NOISE LEVELS



UC013G 40V Max Chain Saw



- Delivers power of a 42cc gas chain saw
- Captured bar nuts retained in sprocket cover
- Lateral chain tensioning with dual stud
- Variable speed trigger and high chain speed

Guide Bar Length 450 mm (18")

Chain Gauge 1.1 / 1.3 mm (0.043 / 0.050")

Chain speed 0 - 5,020 FPM



DUC355 36V Chain Saw



- Delivers power of a 32cc gas chain saw
- Captured bar nuts retained in sprocket cover
- Lateral chain tensioning with dual stud
- Variable speed trigger and high chain speed

Guide Bar Length 350 mm (14")

Chain Gauge 1.1 mm (0.043")

Chain speed 0 - 3,940 FPM

CHAIN SAW ACCESSORIES



191G25-8
Sprocket Guide Bar
16" 3/8" .050



191H12-3
Saw Chain 16" 3/8"
.050" 91PX



191T88-2
Sprocket Guide Bar
16" .325 0.043



191T92-1
Saw Chain 16"
.325, 0.043



191X03-0
Sprocket Guide Bar
18" .325 0.043



191X04-8
Saw Chain 18"
.325 0.043

For DUC306, DUC406, DUC407 DUC353,
DUC355, UC004G, UC013G

For DUC353, DUC355, UC013G

For UC013G



XGT **BL MOTOR XPT AFT**
HP001G
 40V Max Hammer Drill

- Electronic digital clutch (41 settings in low speed, 21 settings in high speed)

Chuck capacity 13 mm (1/2")
Max Torque 125 N·m (1,100 in.lbs.)
0 - 650 / 0 - 2,600 RPM
0 - 9,750 / 0 - 39,000 IPM



XGT **BL MOTOR XPT ADT**
DA001G
 40V Max Angle Drill

- Drills up to 159 mm (6-1/4") holes
- Soft start feature for smooth start-ups

Chuck capacity 13 mm (1/2")
Max Torque High: 55 N·m (487 in.lbs) Low: 136 N·m (1,210 in.lbs.)
0 - 400 / 0 - 1,500 RPM



XGT **BL MOTOR XPT**
TW007G
 40V Max Impact Wrench

- 3 forward and 3 reverse Auto-Stop modes
- Compact and ergonomic design

Square Drive 12.7 mm (1/2")
Max Torque 760 N·m (560 ft.lbs.)
Nut Busting Torque 1,100 N·m (810 ft.lbs.)
0 - 600 / 1,200 / 1,900 / 2,300 RPM
0 - 1,200 / 1,900 / 2,700 / 2,900 IPM



XGT **BL MOTOR XPT**
TW001G
 40V Max Impact Wrench

- 3 forward and 3 reverse Auto-Stop modes
- Higher torque and more compact

Square Drive 19 mm (3/4")
Max Torque 1,800 N·m (1,330 ft.lbs.)
Nut Busting Torque 2,050 N·m (1,510 ft.lbs.)
0 - 950 / 1,150 / 1,400 / 1,800 RPM
0 - 1,900 / 2,200 / 2,400 / 2,500 IPM



LXI **BL MOTOR XPT**
DHP486
 18V Hammer Drill

- 2-speed transmission
- Compact and ergonomic design
- All metal 1/2" self ratcheting chuck

Chuck capacity 13 mm (1/2")
Max Torque 125 N·m (1,100 in.lbs.)
0 - 550 / 0 - 2,100 RPM
0 - 8,250 / 0 - 31,500 IPM



LXI **BL MOTOR XPT ADT**
DDA450
 18V Angle Drill

- Drills up to 127 mm (5") holes
- Soft start feature for smooth start-ups
- Electric brake for maximum productivity

Chuck capacity 13 mm (1/2")
Max Torque High: 26 N·m (230 in.lbs.) Low: 70 N·m (620 in.lbs.)
0 - 450 / 0 - 1,400 RPM



LXI **BL MOTOR**
DTW800
 18V Impact Wrench

- Precise fastening control
- 3-speed power selection switch
- Compact and ergonomic design

Hex Shank 11.1 mm (7/16")
Max Torque 800 N·m (590 ft.lbs.)
0 - 900 / 1,000 / 1,800 RPM
0 - 1,800 / 2,000 / 2,200 IPM



LXI **BL MOTOR XPT**
DTW700
 18V Impact Wrench

- 3 forward and 3 reverse Auto-Stop
- 4-speed power selection for precise fastening control in a wide range of applications

Square Drive 12.7 mm (1/2")
Max Torque 700 N·m (520 ft.lbs.)
Nut Busting Torque 1,000 N·m (740 ft.lbs.)
0 - 500 / 1,200 / 1,900 / 2,200 RPM
0 - 1,000 / 1,700 / 2,400 / 2,700 IPM



LXI **BL MOTOR**
DTW1002
 18V Impact Wrench

- 3-speed power selection switch
- 1/2" anvil with friction ring for quick and easy socket changes

Square Drive 12.7 mm (1/2")
Max Torque 1,200 N·m (890 ft.lbs.)
Nut Busting Torque 1,600 N·m (1,180 ft.lbs.)
0 - 900 / 1,000 / 1,800 RPM
0 - 1,800 / 2,000 / 2,200 IPM



LXI **BL MOTOR**
DTW1001
 18V Impact Wrench

- 3-speed power selection switch
- 3/4" anvil with friction ring and thru hole retention system for maximum productivity

Square Drive 19 mm (3/4")
Max Torque 1,250 N·m (920 ft.lbs.)
Nut Busting Torque 1,700 N·m (1,250 ft.lbs.)
0 - 900 / 1,000 / 1,800 RPM
0 - 1,800 / 2,000 / 2,200 IPM



CW001G

IDEAL FOR USE ON THE JOB SITE OR ON THE ROAD. IT IS ABLE TO STORE UP TO FOUR 2 L PLASTIC BOTTLES OR TWENTY 500 ML PLASTIC BOTTLES



XGT
CW001G
40V Max 20 L (5.3 gal) Cooler & Warmer

- Powered by 4 sources: 40V battery and 18V battery (two in parallel or one), 12V/24V DC (cigar socket), AC.
- 7 Cooling temperature settings and 7 Warming temperature settings

Cooling capacity from -18 to 10°C (0 to 50°F)

Warming capacity from 30 to 60°C (85 to 140°F)



XGT
KT001G
40V Max Hot Water Kettle

- Powered by 40V battery (two in parallel or one)
- Audible buzzer and two color L.E.D. on/off switch indicates the status of the kettle
- Dual layer construction
- Boil-dry protection and Auto shut-off

Water Tank Capacity 800 mL

Boils 800ml (27 oz.) of water in 8 min.



XGT
CF001G
40V Max 235 mm (9-1/4") Fan

- Three speed settings and Oscillation selector for optimal air velocity and control
- Manually tilts 90° up and 45° down
- Automatically oscillates 45° right and left
- 3-stage automatic timer

Air Flow 5.2 / 6.5 / 8.2 m3/min

Max Air Velocity 120 / 150 / 190 m/min



LXT

DFV210
18V Fan Vest

BL MOTOR

- Stay cool in hot harsh job site environments
- 100% polyester – High water repellency
- Powerful fan provides air flow to help evaporate sweat
- Drawcord on hem for adjustable fit

Air Flow 1.5 / 1.7 / 2.1 / 2.2 m³/min

Different size options



LXT

DCW180
18V 20 L (5.3 gal) Cooler & Warmer

- Powered by 3 sources: 18V battery (two in parallel or one), 12V/24V DC (cigar socket), AC
- 5 Cooling temperature settings and 2 Warming temperature settings
- Water-resistant construction (IPX4 rated)

Cooling capacity from -18 to 10°C (0 to 50°F)

Warming capacity 55 / 60°C (130 / 140°F)



LXT

DCM501
18V Coffee Maker

- No paper filter needed
- Compatible with both 12V and 18V batteries
- Brews one 160mL (5 oz.) cup of coffee in 5 minutes
- Boil dry protection

Water Tank Capacity 240 mL

Uses single-serve packs or ground coffee



LXT

DCF102
18V 180 mm (7-1/8") Fan

- Three speed settings and Oscillation selector
- Reduced wind noise level for quiet operation
- Manually tilts 90° up and 45° down
- Automatically oscillates 45° right and left
- 3-stage automatic timer

Air Flow 3.0 / 3.8 / 4.6 m³/min

Max Air Volume 162 CFM



LXT

DCF203
18V 235 mm (9-1/4") Fan

- Three speed settings and Oscillation selector
- Reduced wind noise level for quiet operation
- Manually tilts 90° up and 45° down
- Automatically oscillates 45° right and left
- 3-stage automatic timer

Air Flow 5.2 / 6.5 / 8.2 m³/min

Max Air Velocity 120 / 150 / 190 m/min



LXT

DCF201
18V 250 mm (9-7/8") Fan

- Two speed settings
- Protective bumpers for increased durability
- 45° adjustable platform
- 3-stage automatic timer
- Large carrying handle

Max. Air Volume 5.0m³/min

Max Air Velocity 90 / 120 m/min



LXT

DMR055
18V Radio/Lantern

- Multi functions: Lantern, FM/AM radio, flashlight, USB output port
- 9 programmable stations each for AM and FM radio
- Warm white light tone and color

Illuminance (High): 130 lx or more

Luminous flux (High): 260 lm or more



LXT

DMR114
18V Bluetooth Radio

- Compatible with both 12V and 18V batteries
- Equipped with Bluetooth to wirelessly connect your mobile device to play music
- Delivers rich, full stereo sound from two powerful 2.5" side-firing speakers and one 4" subwoofer

Frequency Band 87.5 - 108 MHz / 522 - 1,710 kHz

USB port for charging your mobile device



LXT

DMR300
18V Bluetooth Radio

- Compatible with both 12V and 18V batteries
- Equipped with Bluetooth to wirelessly connect your mobile device to play music
- Delivers rich stereo sound from two powerful 3.5" side-firing speakers

Frequency Band FM / AM: 87.5 - 108 MHz / 520 - 1,710 kHz

Two USB ports for charging mobile devices



XPT

XGT
ML007G
40V Max LED Flashlight

- 4-mode operation: Spot, Flood, Spot/Flood and Strobe
- 90° pivoting head
- Long beam distance up to 640m

Illuminance Spot / Flood / Spot-Flood:
82,000 / 520 / 60,000 lx

Luminous flux Spot / Flood / Spot-Flood:
600 / 1,000 / 1,250 lm



XGT
ML005G
40V Max LED Work Light

- 3 Brightness Settings
- Compatible with 40V max and 18V batteries
- Dust / water-resistant construction (IP65 rated)
- Angle adjusting knobs

Illuminance at 1m from the light source
(High / Mid / Low): 2,100 / 1,000 / 500 lx

Luminous flux (High / Mid / Low):
3,600 / 1,800 / 900 lm



XGT
ML009G
40V Max LED Work Light

- 3 Brightness Settings
- Compatible with 40V max and 18V batteries
- Dust / water-resistant construction (IP65 rated)
- Angle adjusting knobs

Illuminance at 1m from the light source
(High / Mid / Low): 4,300 / 1,900 / 1,000 lx

Luminous flux (High / Mid / Low):
10,000 / 4,000 / 2,000 lm



XPT

LXT
DML812
18V LED Flashlight

- 4-mode operation: Spot, Flood, Spot/Flood and Strobe
- 90° pivoting head
- Long beam distance up to 640m

Illuminance Spot / Flood / Spot-Flood:
71,000 / 520 / 51,000 lx

Luminous flux Spot / Flood / Spot-Flood:
600 / 1,000 / 1,250 lm



LXT
DML811
18V LED Work Light

- 3 Brightness Settings
- 18V Battery or corded operation
- Dust / water-resistant construction (IP65 rated)
- Angle adjusting knobs

Illuminance at 1m from the light source
(High / Mid / Low): 1,800 / 800 / 350 lx

Luminous flux (High / Mid / Low):
3,000 / 1,500 / 750 lm



LXT
DML814
18V LED Tower Work Light

- 3 Brightness Settings
- Extends to an overall height of 2,240mm (7-1/4 ft)
- Dust / water-resistant construction (IP65 rated)
- Adjustable light heads rotate 180° vertically

Illuminance at 1m from the light source
(High / Mid / Low): 1,250 / 750 / 400 lx

Luminous flux (High / Mid / Low):
3,000 / 1,700 / 900 lm



LXT
X2 18V + 18V 36V
DML810
36V Upright LED Area Light

- 3 Brightness Settings and 3 illumination range modes: 360°, left 180°, and right 180°
- Self-righting design
- Dust / water-resistant construction (IP54 rated)

Illuminance at 1m from the light source
(High / Mid / Low): 550 / 300 / 150 lx

Luminous flux (High / Mid / Low):
5,500 / 3,000 / 1,500 lm



LXT
X2 18V + 18V 36V
DML809
36V LED Work Light

- 3 Brightness Settings
- 2X 18V Batteries or corded operation
- Dust / water-resistant construction (IP65 rated)
- Angle adjusting knobs

Illuminance at 1m from the light source
(High / Mid / Low): 3,800 / 1,500 / 800 lx

Luminous flux (High / Mid / Low):
10,000 / 4,000 / 2,000 lm

ACCESSORIES



GM00002073
Tripod for
DML809 / DML811 / ML005G / ML009G



FitKnit™ Cut Level 1 Nitrile Coated Dipped Gloves

- High abrasion resistance for increased performance
- Touchscreen compatible for phone and tablet use

T-04117 (Small/Medium)
T-04123 (Large/X-Large)



Open Cuff Flex Protection Utility Work Gloves

- High dexterity for flexibility, easy movement, and better control
- Touchscreen compatible for phone and tablet use

T-04151 (Medium)
T-04167 (Large)
T-04173 (X-Large)



Advanced Impact Demolition Gloves

- Up to 20% more thermoplastic rubber (TPR) for increased impact protection
- Touchscreen compatible for phone and tablet use

T-04248 (Medium)
T-04254 (Large)
T-04260 (X-Large)



BATTERIES & CHARGERS



22 MIN.
CHARGE TIME



28 MIN.
CHARGE TIME



45 MIN.
CHARGE TIME



HIGH OUTPUT
BATTERY

45 MIN.
CHARGE TIME



50 MIN.
CHARGE TIME



**2X LONGER
RUN TIME**

76 MIN.
CHARGE TIME

COMPACT SIZE

LONGER RUN TIME

2.0Ah Battery
191L29-0
BL4020

2.5Ah Battery
191B36-3
BL4025

4.0Ah Battery
191B26-6
BL4040

4.0Ah Battery
1910N6-8
BL4040F

5.0Ah Battery
191L47-8
BL4050F

8.0Ah Battery
191X65-8
BL4080F



DC40RC
Standard Charger
191M85-6 (120V) / 191M90-3 (240V)



DC40RA
Rapid Charger
191F37-5 (120V) / 191E07-8 (240V)



DC40RB
Dual Port Charger
191N04-8 (120V) / 191N09-8 (240V)

COMPATIBILITY

ADP10 (191C09-2)



Adapts 40V max XGT
chargers to charge 18V
LXT batteries

LXT BATTERIES & CHARGERS



FASTER CHARGE TIME

HIGHEST OUTPUT

1.5Ah Battery
196235-0
BL1815N

2.0Ah Battery
197254-9
BL1820B

3.0Ah Battery
197599-5
BL1830B

4.0Ah Battery
197267-0
BL1840B

5.0Ah Battery
197280-8
BL1850B

6.0Ah Battery
632F69-8
BL1860B



DC18SD
Standard Charger
630567-0 (120V) / 630570-1 (240V)



DC18RC
Rapid Charger
196433-6 (120V) / 195584-2 (220V)



DC18SE
Automotive Charger
194618-8



DC18RD
Dual Port Charger
196963-7 (120V) / 196933-6 (220V)



DC18SF
4-Port Charger
196426-3

Makita



SCAN ME



MAKITALATINAMERICA